

G



### Features

- Low cost
- Scales are direct reading for water
- Detachable, clear acrylic scale plate mounts directly on front of metering tube.
- Silk screened printing to enhance readability

### Specifications

Model	Measuring range			Thread (F/BSP)	Weights (KG)	Working pressure (Mpa)	Accuracy	Working temperature °C
	GPM	LPM	LPH <sub>(optional)</sub>					
Z-4001	0.2~2	1~7	50~400	1/2"	0.2	≤0.6	±6%	≤55°C
Z-4002	0.5~5	1.8~18	100~1000	1/2"				
Z-4003	1~10	4~36	250~2400	3/4"				
Z-4004	2~20	10~70	500~4000	1"	0.65			
Z-4005	5~30	20~110	1000~6000	1"				
Z-4006	20~60	80~220	4000~13000	1½" male	1.4			
Z-4007	30~110	100~400	6000~25000	2"				
Z-4008	50~150	180~600	12000~35000	2"				
Z-4009	60~200	200~800	12000~50000	2"				

Note: NPT standard is optional of 304SS fittings.

### Sizes

Unit: mm

Model	Z-4001	Z-4002	Z-4003	Z-4004	Z-4005	Z-4006	Z-4007	Z-4008	Z-4009
A	210	210	278	265	265	306	345	345	345
B	32	32	45	51	51	51	75	75	75
C	Joint (PP) or 1Cr18Ni9Ti(304SS)								
D	O-ring(Silicon rubber or fluoro rubber)					O-ring(Nitrile rubber)			
E	Blocking ring (ABS)					101 (Nylon)			
F	Float 1Cr18Ni9Ti(304SS)								
G	Guide rod ( 304SS )								
H	Body(Acrylic)								

