

Specifications

Accuracy : ±5%

Tube material : PC (Polycarbonate)

Float material : ABS, SS316

Guide rod material : SS316

O-Ring : EPDM

Working pressure : 6 bar

Working temperature : 60°C

End connection : Socket, female, Flange

Option : Lower / Upper limit switch



Model	Water flow range		Socket (สวมทากาว)	Male Thread (เกลียวนอก)	Female Thread (เกลียวใน)	Flange (หน้าแปลน)
	GPM	LPM				
Z-5008 (316 SS Float)	0.1-1 0.2-2 0.5-5	0.5-4 1-7 1.8-18	--	½"NPT	½"BSP	--
Z-5008C (316 SS Float)	0.1-1 0.2-2 0.5-5	0.5-4 1-7 1.8-18	Thai Pipe Sch.80 UPVC Pipe	½"NPT	½"BSP	--
Z-5015 (316 SS Float)	0.25-2.5 0.5-5 0.8-8	1-10 1.8-18 3-30	Thai Pipe Sch.80 UPVC Pipe	--	½"BSP	--
Z-5025 (ABS Float)	0.8-8 1-10	3-30 4-40	Thai Pipe Sch.80 UPVC Pipe	--	¾"BSP	--
Z-5032 (ABS Float)	1.2-12 2-20 2.5-25	5-50 8-80 10-100	Thai Pipe Sch.80 UPVC Pipe	--	1"BSP	1" ANSI/JIS
Z-5050 (ABS Float)	2.5-25 5-45 7-70	10-100 20-180 25-250	Thai Pipe Sch.80 UPVC Pipe	--	2"BSP	1 ½" ANSI/JIS 2" ANSI/JIS
Z-5065 (ABS Float)	25-110 40-160 50-250	80-400 150-650 200-1000	Thai Pipe Sch.80 UPVC Pipe	--	2 ½"NPT	2" ANSI/JIS 2 ½" ANSI/JIS



Z-500 Series Dimensions (mm)

Model	L	D	B2	L1 (Socket) สวมทากาว	L2 (Male) เกลียวนอก	L3 (Female) เกลียวใน	B1	
							ANSI Sch.80	Thai pipe
Z-5008	99	42	26	146	170	--	21.34	22±0.15
Z-5008C	160	51	26	210	230	209	21.34	22±0.15
Z-5015	135	51	26	180	210	183	21.34	22±0.15
Z-5025	170	59	39	226	253	228	33.40	34±0.15
Z-5032	223	72	49	287	317	287	42.16	42±0.15
Z-5050	290	100	73	375	400	370	60.33	60±0.15
Z-5065	325	120	89	420	--	423	73.03	76±0.15

